NASA Technical Paper 2069

August 1982

Atmospheric Constraint Statistics for the Space Shuttle Mission Planning

O. E. Smith, G. W. Batts, and J. A. Willett



(NASA-1P-2)09) AIMOSEBERTO CONSTRAINT STATISTICS FOR THE SPACE SHOTTLE MISSION PLANNING (NACA) 33 P MC AUG/ME ADT CSCI 22A

382-33417

Jnclus
H1/16 34500



NASA Technical Paper 2069

1982

Atmospheric Constraint Statistics for the Space Shuttle Mission Planning

O. E. Smith

George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama

G. W. Batts and J. A. Willett

Computer Sciences Corporation Huntsville, Alabama



Scientific and Technical Information Branch

ACKNOWLEDGMENTS

Recognition is extended to Mr. James R. Bates, Flight Requirements Office, and Mr. C. C. Gay, Operations Integration Office, of the Johnson Space Center for providing the Space Shuttle launch and flight mission rules for the atmospheric restrictions and the many helpful technical discussions in translating the rule requirements into atmospheric constraints. As users of the mission analysis statistics products, they have contributed to the scope and organization of the attending computer programs.

TABLE OF CONTENTS

		Page
l.	INTRODUCTION	1
11.	COMPUTER SYSTEM DESCRIPTION	2
	A. Atmospheric Data Bases	2
	B. Atmospheric Constraints by Mission Phases	2
	C. Techniques	3
Ш.	ILLUSTRATIVE EXAMPLES	5
	A. Example for Launch, RTLS, and Prelaunch	5 7
	B. KSC EOM Trade Study Examples	7
IV.	CONCLUSIONS/RECOMMENDATIONS	11
REF	ERFNCFS	32

LIST OF TABLES

Table	Title	Page
la.	Probability of Atmospheric Constraints for KSC Launch Operations for March	12
lb.	Probability of Atmospheric Constraints for KSC Return to Launch Site for March	13
lc.	Probability of Atmospheric Constraints for Prelaunch Operations for KSC for March	14
2.	Probability of Case I Atmospheric Constraints for EOM Landing at KSC, January	15
3.	Probability of Case I Atmospheric Constraints for EOM Landing at KSC, July	16
4.	Probability of No-Go for Any One of Case I Atmospheric Constraints For EOM Landing at KSC for All Months	17
5.	Probability of Case II Atmospheric Constraints for EOM Landing at KSC, January	18
6.	Probability of Case II Atmospheric Constraints for EOM Landing at KSC, July	19
7.	Probability of Case II, Any One of Atmospheric Constraints for EOM Landing At KSC For All Months.	20
8.	No-Go and Go for Case I Atmospheric Constraints for KSC EOM Landing at 0900 LST, January	21
9.	Probability of No-Go Runs and Conditional Probabilities for Any One of Case I Atmospheric Constraints for KSC EOM Landing at 0900 LST, January	22
10.	Probability of Go Runs and Conditional Probabilities for Any One of Case I Atmospheric Constraints for KSC EOM Landing at 0900 LST, January	23

LIST OF ILLUSTRATIONS

rigure	ritte	rage
1.	Conditional No-Go probabilities for Case I atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January	24
2.	Conditional Go probabilities for Case 1 atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January	25
3.	Conditional No-Go probabilities for Case I atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July	26
4.	Conditional Go probabilities for Case I atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July	27
5.	Conditional No-Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January	28
6.	Conditional Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January	29
7.	Conditional No-Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July.	30
8.	Conditional Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July	31

TECHNICAL PAPER

ATMOSPHERIC CONSTRAINT STATISTICS FOR THE SPACE SHUTTLE MISSION PLANNING

I. INTRODUCTION

This report describes the procedures that have proven to be effective in addressing specific questions on the frequency of atmospheric conditions of interest for the Space Shuttle mission planning. There are several atmospheric parameters of interest for each of the mission phases. The mission phases considered are (1) pre-launch, (2) launch operations, (3) return to launch site (RTLS), (4) abort once around (AOA), and (5) end of mission landing (EOM). Most standard statistical summaries of atmospheric variables are tabulated for single variables or a combination of a few variables such as cloud eilings and visibilities. That is, they are parametric statistical summaries. Here, the interest is not only in the probability of each of the several atmospheric variables taken separately, but also in the probability that at least one of several variables will be of concern for a particular mission phase and for the several mission phases. For example, if there is a launch constraint due to several atmospheric parameters of which any one is a No-Go condition, then the probability of interest is the probability that any one of the constraints will occur.

The purpose of the statistical analysis is to address the following questions relative to assigned atmospheric constraints for the Space Shuttle mission phases.

- 1) What is the probability that the assigned atmospheric constraints will (will not) occur during a particular monthly reference period?
- 2) What is the probability that the assigned atmospheric constraints will (will not) occur for N consecutive days at a particular time of day during a monthly reference period?
- 3) Once the assigned atmospheric constraint has occurred (has not occurred) for 1, 2, 3, ... J consecutive days at a particular time of day, what is the probability that the given constraints will continue for N additional days?

Valid answers to these questions have practical applications to the Space Shuttle program in the following interrelated areas:

- 1) Establishing the natural environment design criteria
- 2) Mission planning
- 3) Establishing launch and flight operational rules
- 4) Shuttle program decisions on cost-trade assessments.

All three questions can be adequately answered for the stated purposes provided that appropriate atmospheric data bases are available. Over the years of assigned roles, this organization has developed sufficiently long periods of atmospheric records to use empirical statistical methods for the Shuttle launch from the Kennedy Space Center (KSC) with the AOA and EOM at Edwards Air Force Base and Northrup Strip or AOA and EOM at KSC.

The first question, "What is the frequency?" is answered by simple empirical probabilities. The second and third questions on the continuation of atmospheric events are answered using empirical probabilities of runs and conditional probabilities.

It soon became apparent after issuing a report [1] that the Shuttle Program Office and the Mission Planning Office at the Johnson Space Center had requirements for answers to many specific questions on the atmospheric conditions. The choice was made to establish computer programs with many options to address these questions. Otherwise a very large volume of statistical tabulations to meet the expanding needs would be required — an impractical approach.

The operations of the Atmospheric Mission Analysis computer programs have been performed to give statistical tabulations for assigned atmospheric constraints routinely on a 24-hr basis. The usage rate has been approximately 30 cases per month over the past year.

Section II gives a brief description of the atmospheric data bases, the atmospheric constraints options by mission phases, and the computer programs. Section III presents illustrative examples to demonstrate a few of the many possible statistical tabulations.

II. COMPUTER SYSTEM DESCRIPTION

A. Atmospheric Data Bases

- 1. <u>KSC</u>. The surface data used for this site is the WBAN hourly surface observations (Deck 144). The upper altitude wind data used is the two observations per day (Deck 600). The thunderstorm data used is the TD9688 data. The peak surface wind data used is the TD9690 data. All data used covered hours 0 through 23 with the exception of the upper altitude winds which were interpolated from the two observations per day to hourly observations. Period of record is January 1, 1957, through December 31, 1970.
- 2. Edwards Air Force Base. Data used for this site is the WBAN hourly surface observations (Deck 144). Period of record is January 1, 1957, through December 31, 1970.
- 3. Northrup Strip. Data used for this site is the WBAN hourly surface observations (Deck 144). Period of record is January 1, 1957, through December 31, 1970.
- 4. Vandenberg Air Force Base. The surface data used for this site is the WBAN hourly surface observations (Deck 144). The upper altitude wind data used is the two observations per day (Deck 600) which were interpolated to hourly observations. Period of record is January 1, 1965, through December 31, 1973.

B. Atmospheric Constraints by Mission Phases

- 1. <u>Prelaunch Phase at KSC</u>. There is one constraint for the prelaunch phase. There cannot be any precipitation during the hours of prelaunch activity. The beginning and ending hours for prelaunch activity are variable parameters.
 - 2. Launch Phase at KSC. There are six constraint categories for the launch phase:

- 1) Thunderstorm No-GO if a thunderstorm occurs.
- 2) Precipitation No-Go if precipitation occurs.

- 15, E

- 3) Cloud ceiling and/or visibility No-Go if the cloud ceiling is lower than specified and/or if the visibility is less than specified.
 - 4) Peak surface wind speed No-Go if the peak surface speed is greater than specified.
- 5) Upper altitude winds No-Go if the max Q is greater than the specified U* for the specified altitude region at the specified azimuth.
- 6) Tower clearance No-Go if the peak surface wind is greater than specified for the wind direction. Wind from the directions of 150 to 210 degrees has a specified maximum while wind from all other directions may have a different specified maximum.
 - 3. RTLS Phase. There are eight constraint categories for the RTLS phase:
 - 1) Thunderstorm Same as launch phase.
 - 2) Precipitation Same as launch phase.
- 3) Cloud ceiling and/or visibility Same as launch phase except cloud cover may optionally be used instead of cloud ceiling.
 - 4) Visibility No-Go if visibility is less than specified.
 - 5) Cloud cover No-Go if cloud cover is greater than specified.
 - 6) Head/tail wind No-Go if the head or tail wind is greater than specified.
 - 7) Steady state crosswind No-Go if the steady state crosswind is greater than specified.
 - 8) Peak crosswind No-Go if the peak crosswind is greater than specified.
 - 4. AOA. Same as for RTLS using the data base for the desired landing site.
 - 5. EOM. Same as for RTLS using the data base for the desired landing site.

C. Techniques

- 1. Single Site. The desired analysis is performed on one site independently. For a KSC launch, the prelaunch, launch, and RTLS phases are for KSC only. An AOA or EOM phase may be performed on either Edwards Air Force Base, Northrup Strip, or KSC independent of each other.
- 2. <u>Multiple Sites</u>. The desired analysis is performed using all sites with each phase being dependent upon a Go condition for the previous phase. For example, the launch phase is only analyzed for those cases which are a Go condition from the prelaunch phase. The RTLS phase is only analyzed for those cases which are a Go condition from the launch phase. The AOA phase is only analyzed for those cases which are a Go

condition from the RTLS phase. The AOA phase uses each of the landing sites independently as well as jointly. Also, this technique allows for a launch window rather than a set launch hour.

- 3. Options. For the single site analysis, there are a total of 28 options which may be exercised at run time. Two of these options are for prelaunch operations, 15 options for the launch operations, and 11 options for the RTLS, AOA, or EOM operations.
 - 1) Prelaunch operation beginning hour.
 - 2) Prelaunch operation ending hour.
 - 3) Launch thunderstorm constraint.
 - 4) Launch precipitation constraint.
 - 5) Launch cloud ceiling constraint.
 - 6) Launch visibility constraint.
 - 7) Launch surface peak wind speed constraint.
 - 8) Launch azimuth for upper winds analysis.
 - 9) Launch upper winds beginning altitude.
 - 10) Launch upper winds ending altitude.
 - 11) Launch U* constraint for upper winds.
 - 12) Launch option to disregard upper winds.
 - 13) Launch tower clearance minimum wind direction.
 - 14) Launch tower clearance maximum wind direction.
- 15) Launch tower clearance wind speed constraint for the winds occurring between the minimum and maximum wind direction.
- 16) Launch tower clearance wind speed constraint for the winds occurring at all other wind directions.
- 17) Launch wind type to be used for head/tail wind constraint (either steady state or peak winds may be used).
- 18) RTLS, AOA, and EOM runway angles which allow for up to two runways with the option to use any combination of landing directions.
 - 19) RTLS, AOA, and EOM thunderstorm constraint.
 - 20) RTLS, AOA, and EOM precipitation constraint.

- 21) RTLS, AOA, and EOM option to use either the cloud ceiling or cloud cover constraint.
- 22) RTLS, AOA, and EOM cloud ceiling constraint.
- 23) RTLS, AOA, and EOM visibility constraint.
- 24) RTLS, AOA, and EOM cloud cover constraint.
- 25) RTLS, AOA, and EOM head wind constraint.
- 26) RTLS, AOA, and EOM tail wind constraint.
- 27) RTLS, AOA. and EOM steady state crosswind constraint.
- 28) RTLS, AOA, and EOM peak crosswind constraint.

For the multiple site analysis, all of the above options apply plus the launch window time and the order of landing sites desired for AOA and EOM.

4. Analysis of Runs and Time Conditional Probabilities. This analysis provides the capability of determining the Go or No-Go status for each day of the month for each year of the data sample. These are then analyzed to give the length of runs for both Go and No-Go, if a given day is No-Go, what is the probability of succeeding days being a Go; or, if a given day is Go, what is the probability of succeeding days being Go or No-Go.

III. ILLUSTRATIVE EXAMPLES

This section presents illustrative examples for the probability of atmospheric constraints for launch, return to launch site, and prelaunch for a March 0800 LST launch from the KSC. Another set of examples is given for the end of mission landing atmospheric constraints to illustrate the frequency of occurrence, runs probabilities, and time conditional probabilities.

A. Example for Launch, RTLS, and Prelaunch

These examples are for illustrative purpose only. They do not necessarily represent the atmospheric constraints for any particular orbiter configuration.

- 1. Probability of Atmosphe ic Constraints for KSC Launch Operations for March (Table 1.a). For this example, there are five assigned atmospheric constraints. The body of the table gives the percentage probability for the occurrence for each of the five constraints for each hour of the day versus local standard time. For brevity, this table is also called No-Go probabilities for launch operations. The Go probabilities in percent would be these values subtracted from 100 percent. There must be some rationale in the selection of the atmospheric constraints:
- 1) The thunderstorm constraint is set by the Space Shuttle program design requirement. The vehicle is not designed to be launched through a thunderstorm.
- 2) The precipitation constraint is an α rational concern for ice/frost accumulation on the ET. There was also an early concern for rain erosion of β e tiles during ascent.

- 3) The cloud ceiling and visibility constraint is an early range safety constraint established to meet the requirement for visual sighting in the first 1600 ft of flight by a camera located 5 miles from the launch complex.
- 4) The peak wind speed has been eliminated from this example by setting the value above the observed range of this variable; i.e., > 99 knots.
- 5) The upper winds constraint is an algorithm for the maximum d mamic pressure constraint. In this example, the 25-m/sec wind component in the 10- to 15-km altitude region is a head wind component relative to the monthly mean in-plane wind component for the flight azimuth of 59 degrees.
- 6) The tower clearance peak surface wind ≥ 20 knots from the south plus and minus 30 degrees and greater than 28.7 knots for all other wind directions has been established as a facilities design limit.

The last line in Table 1.a gives the percentage probability of No-Go for the occurrence of one or more of the above listed constraints. Note that the occurrences of the individual constraints are not mutually exclusively events. The sum of the probability of the individual constraints exceeds, in some cases, the last entry in this table.

- 2. Probability of Atmospheric Constraints for KSC Return to Launch Site (RTLS) for March (Table 1.b). For this example, the selected atmospheric constraints are:
 - 1) The occurrence of a thunderstorm.
 - 2) The occurrence of precipitation.
 - 3) A cloud ceiling ≤ 5000 ft and/or visibility ≤ 8 n.mi.
 - 4) There is a separate breakout for the visibility ≤ 8 n.mi.
- 5) Cloud cover > 0.5. A cloud ceiling is defined as the height at which 0.6 or more of the sky is obscured by clouds. The concern for cloud cover and visibility is the desire of the flight crew to be able to see the runway in the event of an RTLS.
- 6) For peak runway winds, a head wind > 20 knots and/or a tail wind > 20 knots is selected for an orbiter flight test. Note, from the heading of this table, both ends of the runway are used in this example; therefore, there is no tail wind occurrence.
- 7) The surface steady state crosswind has been eliminated from this example by setting the value > 99 knots.
- 8) The peak crosswind to the runway > 10 knots in this example was selected for an orbiter flight test.

The entry entitled "Any of the Above" is the probability of occurrence of one or more of the above constraints for the RTLS.

The last entry in Table 1.b, entitled "Any of the Above for Launch and RTLS," is the probability for No-Go if any one of the above listed constraints for launch and RTLS is considered as a No-Go condition.

Here it is noted, again, that these constraints are not mutually exclusive events.

3. Probability of Atmospheric Constraints for Prelaunch Operations for KSC for March (Table 1.2). The only prelaunch constraint considered is the occurrence of precipitation at any time after the external tank (ET) loading until launch time. This is because there is concern that ice will form on the ET if precipitation occurs. The concern is that the ice will fall off during ascent and damage the orbiter tiles. In this example, there is a 15 percent chance that precipitation will occur at least one time between the hours of 0200 and 0800 LST. This gives an overall No-Go probability of 73 percent for an 0800 LST March launch for the stated atmospheric constraints for prelaunch, launch, and RTLS

For the future prelaunch statistical analysis for Vandenberg Air Force Base, a different approach will be used for the ET ice constraint. A thermal transfer simulation has been made using the atmospheric variables for Vandenberg Air Force Base to determine the amount of ice accumulated for each hour of the day for various exposure periods. The prelaunch constraint for the ET ice will be made in terms of an ice thickness constraint. The assigned ice thickness will be treated in a statistical manner as any other atmospheric variable.

The examples given for No-Go probabilities in Tables 1.a through 1.c are intended for instructive purposes only. The assigned atmospheric constraints and their values are not to be construed as mission rules. The resulting probabilities are more accurately interpreted as the chances there will be concern for the operating restriction. For example, the launch mission rule may read no launch through a thunderstorm. The meteorological data base gives only the occurrence of thunderstorms and a thunderstorm is reported only when thunder is heard. Thunder is heard over a radius of approximately 10 miles. During operations, there is certainly a reason to be concerned when a thunderstorm is reported. Additional information is required, e.g., where is the thunderstorm in relation to the vehicle flight path, the time of the report, and expected thunderstorm movement.

The range safety requirement rule is for visual sighting of the flight in the first 1600 ft from a position 5 miles from the launch complex. A translation of this rule is made in terms of a cloud ceiling and visibility. The rationale for other atmospheric constraints is similarly interpretations of operating restrictions. Certainly, the statistics given in the mission analysis programs are the chance there will be concerns for the Shuttle operating restrictions as related to atmospheric conditions. Any number of atmospheric constraint limits and options to the computer programs can be exercised to make relative comparisons of various translations of operating restrictions in terms of the available atmospheric data bases.

B. KSC EOM Trade Study Examples

Two sets of atmospheric constraints for EOM landing at FSC are presented to illustrate a trade study analysis for mission planning. These two sets of atmospheric constraints are designated as Case I and Case II throughout the following discussion.

The Case I atmospheric constraints are:

- Thunderstorm occurrence.
- 2) Precipitation occurrence.
- 3) Cloud ceiling $\leq 20,000$ ft and/or visibility less than 8 n.mi.

- 4) Runway winds: peak head wind > 25 knots. (Since both ends of the runway are used, there is no tail wind constraint.)
 - 5) Peak cross runway wind > 10 knots.

The Case II atmospheric constraints are the same as Case I except steady state runway winds are used.

The Shuttle mission planning questions addressed are:

- 1) For two sets of atmospheric constraints for landing at KSC at the EOM, what is the probability each of the constraints occurring and for any one of the constraints occurring?
- 2) For the sets of constrictions, what is the probability of EOM landing delays for N consecutive days at a specified time of day?
- 3) For the sets of constraints, what is the probability of N consecutive additional delay days, given that the EOM landing is delayed for J consecutive days?

Answers to these three questions are illustrated.

1. Probability of Atmospheric Constraints for EOM Landing at KSC, January and July. The percentage probability for No-Go for each of the Case I atmospheric constraints for EOM landing at KSC for each hour local standard time for January and July is presented in Tables 2 and 3. The ceiling and visibility constraint is the most frequent cause for No-Go for landing in January followed by the peak crosswind constraint. Whereas in July, the peak crosswind is the most frequent cause for No-Go for landing. Also, note the high frequency of thunderstorms in the afternoon hours in July. The last line in Tables 2 and 3 gives the probability of No-Go for landing caused by any one of the above listed constraints. A summary chart (Table 4) gives the probability for any one of the Case I atmospheric constraints for all months versus all hours. Here it is seen that the "best" landing times are early morning hours during the summer months and the "worst" times are near noon to midafternoon with 60 percent chance for No-Go for landing in all months except November and December.

To contrast the No-Go probability for the Case I atmospheric constraints presented in Tables 2, 3, and 4, similar tables for the Case II atmospheric constraints are presented as Tables 5, 6, and 7. Here, the contribution to the No-Go probabilities caused by the peak runway wind constraint is noted. All other constraints are the same. From Table 7 there is a 20 to 55 percent chance for No-Go for landing due to one or more of the stated atmospheric constraints.

2. Runs and Time Conditional Probabilities. Tables 8, 9, and 10 are presented to illustrate the techniques for the analysis of runs and conditional probabilities for the Case I atmospheric constraints for the EOM landing at KSC at 0900 hr LST in January.

In Table 8, the entries are consecutive listings of codes "0" for Go and "1" for 1 3-Go for each January day for the 14 years of records. This table gives the No-Go days and Go days for anding for the Case I atmospheric constraints at 0900 hr LST at KSC when any one of the five constraints occurred or did not occur for the 434 days. It is from a listing of Go and No-Go days (Table 8) that Tables 9 and 10 are derived.

A run is a succession of like events or things. An explanation of the computational procedures used to derive Tables 9 and 10 from Table 8 is in order because of the unusual techniques used to count runs and overlapping runs. To illustrate, let there be a sequence, as:

aaa, bb, aaaa, b, aaaaaa, bbbb

There are four runs of a's and three runs of b's. There is one run of a's of length 1, no runs of a's of length 2, two runs of a's of length 3, and one run of a's of length 5. There are three runs of a's of length 3 or more, one run of length 4 or more, and one run of length 5. There are, by counting all possible overlapping lengths of runs, twelve runs of a's of length 1 (i.e., there are twelve a's in the sequence), there are eight runs of length 2, five runs of length 3, two runs of length 4, and one run of length 5.

The computational format for the above counting of runs can be conveniently arranged as in the following:

Illustration for Counting Runs

Length of Run, of Runs of Prob. of Run, Ni Length Ni Number of Runs of Length Ni First Sum Length Ni Sum Sum Length Ni Prob. of a Runs of Prob. of a Runs of Sum Length Ni Number of Runs of Sum Length Ni First Second Sum Sum Length Ni 1 1 1 4 12 0.63 1 3 7 2 0 3 8 0.42 1 2 4 3 2 3 5 0.26 0 1 2 4 0 1 2 0.11 1 1 1	(8)	(7)	(6)	(5)	(4)	(3)	(2)	(1)
2 0 3 8 0.42 1 2 4 3 2 3 5 0.26 0 1 2			Runs of b's of	Run of a of Length			Runs of a's of	of Run,
3 2 3 5 0.26 0 1 2	7	3	1	0.63	12	4	1	1
	4	2	1	0.42	8	3	0	2
4 0 1 2 0.11 1 1 1	2	1	0	0.26	6	3	2	3
	1	1	1	0.11	2	1	0	4
5 1 1 1 0,06 -			-	0.06	1	1	1	5
		Second Sum	First Second Sum	Number of Runs of b's of Sum Length N; 1 3 7 1 2 4	Prob. of a Runs of of Length N _i Number of Runs of b's of Length N _i First Second Sum 0.63 1 3 7 0.42 1 2 4 0.26 0 1 2 0.11 1 1 1	Second Sum Prob. of a Runs of Runs of Sum Sum	First Sum Second Sum Prob. of a Run of a of Length Ni Number of Runs of b's of Length Ni First Sum Second Sum 4 12 0.63 1 3 7 3 8 0.42 1 2 4 3 5 0.26 0 1 2 1 2 0.11 1 1 1	Number of Runs of a's of Length N; First Sum Length N; Second Sum

12 + 7 = 19 = N_T , the number of observations in the sequence.

Now, turning to Table 9, the first column gives the length of run for No-Go for the stated atmospheric constraints. The second column gives the observed number (frequency) of runs of length N, the first column. For example, there was one run of length 13 and there were no runs of length 12. These frequencies are obtained by counting the lengths of runs of 1's in Table 8. In Table 8, there are 14 sequences of length 31. A fun is not continued from one January year to another. The fifth column, heading Probability Percent of No-Go Days, gives the probability there will be No-Go conditions for N consecutive days for the Case I atmospheric constraints for the EOM landing at 0900 LST. For example, there is a 58 percent chance of No-Go for landing at 0900 LST at KSC in January. This is the same probability obtained from the previous computer program for Table 2. There is a 38 percent chance for No-Go landing on two consecutive days at 0900 LST and there is a 13 percent chance for No-Go landing for five consecutive days.

The array of probabilities (Table 9) under the headings J=1, J=2, etc., are the time conditional probabilities. These probabilities are obtained by dividing the N_{i+j} values by N_j in column 4, the second sum column, e.g.,

For J=1, (163/253) 100 = 64 percent , (112/253) 100 = 47 percent , etc.

and for

J=2, (112/163) 100 = 69 percent , (76/163) 100 = 47 percent , etc.

The application of these conditional probabilities is illustrated. Suppose the Shuttle Orbiter is in orbit in January and scheduled to land at KSC at 0900 LST and the Case I atmospheric constraints exist. Now it is a certainty, a probability of 100 percent, there is no landing today; then there is a 64 percent chance (read under the J=1 column) that there will be no landing tomorrow at 0900 LST; and a 44 percent chance for no landing for the day after tomorrow at 0900 LST. Now let it be given that there was no landing yesterday and no landing today due to the Case I atmospheric constraints; then there is a 69 percent chance (read under column J=2) there will be no landing tomorrow at 0900 LST.

Table 10 gives the runs and conditional probabilities for favorable conditions for the KSC EOM landing at 0900 LST for the Class I atmospheric constraints. For example, reading from the fifth column in Table 10, there is a 42 percent chance for landing at 0900 LST in January; there is a 21 percent chance for landing at 0900 LST on two consecutive days, etc. Given that it is favorable for landing today, then there is a 50 percent chance (read under J=1) that the Case I atmospheric constraints will be favorable for landing tomorrow, etc.

The runs and conditional probabilities contained in Tables 1 and 2 are illustrated in Figures 1 and 2. Further, for the Case 1, atmospheric constraints for the EOM landing at KSC at 0900 LST for July are shown in Figures 3 and 4. The straight line labeled P(N) in the figures give the probability for the length of runs for independent events. If the observed probabilities for run lengths were independent from day to day, then there would be close agreement between the observed runs probabilities (labeled with triangles) and the P(N) curve. Further, the observed conditional probabilities would be coincident to the P(N) curve shifted by each unit for J=1, J=2, etc. There is definitely persistence in the Case I atmospheric constraints because there are observed longer runs that would be the case for independent events.

Figures 5, 6, 7, and 8 are the illustrations for the runs and conditional probabilities for the Case II atmospheric constraints for the No-Go and Go statistics for a KSC EOM landing at 0900 LST. In these examples, the observed probability for the run length appears sufficiently close to the P(N) curve to be considered as independent events. However, the rule for independent event does not appear in agreement for the conditional probabilities. Three simple theoretical structures may be considered; viz.

- 1) The probability of the events is constant from day to day.
- 2) The probability of the events is constant after 1 or 2 days.
- 3) The probability of the events is continually increasing from day to day.

Because the run probabilities are so highly dependent on the assigned atmospheric constraints, season, and time of day, there is little hope that a general probability law could apply. Hence, the recommended approach is to use the observed (empirical) probabilities for runs and conditional probabilities.

The application of these statistics to the Space Shuttle operations lies in developing planning strategies. For example, the decision strategy for the EOM landing for the assigned atmospheric constraints would be to prepare for continuation in orbit for several days if unfavorable landing conditions exist. If favorable

landing conditions exist at the EOM, proceed to land at the earliest opportunity. Another strategy is to prepare for an alternative landing site to decrease the risk of landing under unfavorable atmospheric conditions. It is in this planning of operating strategies that there is value in the statistical analysis of runs and conditional probabilities.

1

î

The techniques used to count runs and the computation of conditional probabilities were first introduced for space vehicle applications by O. E. Smith in 1961 and used subsequently by other investigators [2,3] in the analysis of atmospheric data. The technique has proven useful and valid for related applications.

IV. CONCLUSIONS/RECOMMENDATIONS

A capability to furnish in a timely manner specific atmospheric constraint statistics for the Space Shuttle mission phases for management decisions in mission planning and trade studies has been demonstrated. A few examples of the many options for the computer programs have been presented to illustrate the statistical methods. The locations covered by the present capability are for the KSC launch site and for the Edwards Air Force Base and Northrup Strip landing sites. Work is in progress to include the Vandenberg Air Force Base launch site in the mission analysis programs. Additional landing sites, for example AOA sites for Vandenberg Air Force Base launches, and down range abort and landing sites for which there are standard atmospheric data available could be included in the mission analysis programs if the demand develops for these extensions. Further, if the demand develops for more efficient decision aids, then formal decision strategy computer programs could be developed.

A distinction is made between the Space Shuttle operating rules as related to meteorological variables and atmospheric constraints. The atmospheric constraints are translations or interpretations of the Shuttle operating rules so that the probability of occurrence and nonoccurrence of these atmospheric constraints can be obtained from standard historical meteorological data as is available from the national weather services.

It is recommended that the Space Shuttle launch and flight operational rules for atmospheric restrictions be continually reviewed for rule changes. As these rule changes develop, they can be translated into atmospheric constraints and updates for the mission analysis statistics can be performed.

TABLE 1.a. PROBABILITY OF ATMOSPHERIC CONSTRAINTS FOR KSC LATECH OPERATIONS FOR MARCH

AUNCATE 3-16-87 TIM 241 5121	
PELION (RECORD 1957 - 1970 PATA SOURCES : DECK 14	
SEFIALLY COMPLETE THUMBERSICAM PEAM WINDS	
1	PROBABILITIES IN PERCENT
CONSTPATNT /REQUIRF PENT	00 C1 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23
THUNDERSTORM	1 8 2 2 8 2 . 2 . 2
	1 9 7 6 6 6 4 6 5 6 6 5 6 6 6 6 7 9 10 8 7 6
AND GR VISIBILITY	4
PEAK SUPFACE WS	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
C-15 KM	
X2T#UTH = 55.0	3 3 3 2 2 2 2 3 3 3 4 4 3 3 3 3 3 3 3 3
ALF CLEARANCE NY SURFACE NST. T 20.0 ANOTS	
AT 150.0-Z10.0 DEG. BU > 20.7 MNOTS AT ALL OTHER BD	3 3 3 3 3 3 3 3 3 3 3 3 3 3 2 3
ANY OF THE REDWE-	14 16 17 15 15 17 19 20 19 21 20 21 20 18 20 19 21 17 16 18 17 14 13 14

TABLE 1.6. PROBABILITY OF ATMOSPHERIC CONSTRAINTS FOR KSC RETURN TO LAUNCH SITE FOR MARCH

FUN ATE 3-16-82 TIME 20:16:21	16:21
PERICO OF MECCAN 1957 - 1970 DATA SOURCES : DECK 144	
SEGIALLY CHAPLETE THUSDEPSION PEAK WINTS	
PUNKAY ANGLE 155.0 BRY 315.0 DEGREES	
CONSTRAINTZEEDUIPEMENT	¥ 21
THUNCERSTORM	1 1 1 0 1 1 1 0 1 1 1 2 2 2 2 2 2 2 3 2 3 1
PIECIPITATION	OF 9 7 8 01 6 7 9 9 9 9 8 6 6 6 6 6 6 7 9 10 8 7 6 O
CLOUC CEILING C OF = STCS FT AND GR VISIFILITY T BY W WILES	IGINOR
VISIBILITY C E. N. MILES	QUA
CLOUD COVEH	1
PERM SINGS HEAD WIND > 20 KNOTS TAIL WIND > 20 KNOTS	*
SURFRCE CMCSSWING > 99 HACTS-	
PEAK CHOSSHING > ID KNOTS-	7 19 16 16 17 16 18 15 25 29
RMY OF THE RESUL	85 19 09 65 18 18 18 18 14 14 14 15 18 18 18 18 18 18 19 19 19 18 18 18 19 19 19 19 19 19 19 19 19 19 19 19 19
ANY OF THE APONE FOR	61 60 59 61 61 60 66 73 72 75 76 75 81 85 82 81 78 73 64 60 61 61 59

Precipitation 7 7 6 6		
2 2 2 1 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2	אם אא אא אא הא	COMPLEC
	8 7 9 7 9 7	2 - 6
	-	4444444444444444444444444444444444444
ANY OF THE BENYE FOR LEUNCH, PTLS, AND PPELAUNCH	61 63 59 61 61 6C 66 7C 73	

0 Ωï N a О \$ PASE O 13 75 75 ٠, c 9 9 14 7 7 7 7 T ی 2 H 4F 2C 16 7 5 0 2 0 5 Ş -5 o 7 3 5 1 7 0 4 4 0 Œ ... * 35 1 T 0 د 22 ~ o 4 F ی c 30 £ 5 ت £ 5 55 0 0 0 30 ~ H S 3.4 ٥ 0 23 57 Œ . PERCELI 35 Œ M o 0 0 6 a m 8 RETURN TO LAUNCH SITE FOR THE MONTH OF PROBABILITIES IN HB 12 O u o 0 32 28 # 2 28 a Ü lo 0 H ... ~ 32 62 ¥ = 29 4.5 O <u> ۳ ۵</u> 0 0 m 0 5 6.1 £ 2 23 \$ 0 0 2 6 ~ o 2 # 6 2 25 23 3 B ü 16 8 E 29 o 54 0 9 # C 0 62 62 H 60 6 1 a 0 0 15 2 1 9 1 26 E S 50 О o o -0 9 [21 4 S S E ټ 0 ş, 10 0 7 ¥ 3 0 4 M O 0 15 2 0 4 m 2 0 H 20 0 O 17 20 50 # Z 20 0 9 [53 53 4 5 9 5 ¥ 0 0 # 8 PUNEAY FACLE 155.0 AND 335.0 CEGPEES 21:16: PERIOD OF PECORD 1957 - 1970 DATA SOLECES : ANY OF THE ABOVE FOR LAUNCH, RTLS, AND PRELAUNCH CONSTEAT! 17REQUIPEMENT 1111 SECTALLY COMPLETE
THURNERSTORM
PEAK WINDS HEAD LING > 25 KNOTS TAIL LIND > 10 KNOTS THE ABOVE FOR CCCUC CFILING
C OF = 23 CCC FI
AND OF VISIBILITY
C B. N. MILES 4-13-82 SURFACE CPGSSWIND
3 99 FROTS-PEAN CROSSWIND ANY OF THE ALOVE VISIBILITY C C. R. MILES PRECIPITATION FINES THUNDERSTORM CLOUD CCVEP RINDATE ANY OF

TABLE 2. PROBABILITY OF CASE I ATMOSPHERIC CONSTRAINTS FOR EOM LANDING AT KSC, JANUARY

TABLE 3. PROBABILITY OF CASE I ATMOSPHERIC CONSTRAINTS FOR EOM LANDING AT KSC, JULY

The second secon

23 30% 801 Ch ₹0¢ A M £ 8 39 23 47 3 (B) £,2 2 37 64 Hour LST £ 2 36 F 20 38 ý: 4 6 40 7 7 T O 7 4 Case I 51 A B 53 4.1 57 # ~ 52 65 55 4 9 66, 766 63 60 0 40 31.0 **3** £ 2 દ્ધ 5.5 148 4 2 65 20 63 - 63 65 43/ H M 69 65 63 54 / 55 55 85 12 H 23 67 3 603 58 £ = 61 83 59 3, 52 53 £ 0 3 53 58 26 36 21 53 3 59 60 32 # 63 56 57 38 \$5 6 7 H.R. HR. **7** 58 51 25 25 ISC ANY OF THE ABOYE FOR EOM CULCATE 4-13-62 11FE 21:24:11 56 # # 5 25 25 £0 E. 26 ά **.** 9 56 56 55 4.5 54 37 45 50 HR HR 9 46 ... 4 4 4 52 9 7 9 I I H. O3 25 4 1 30 4 32 6 42 45 7 4 5 2 4 A \$ <u>...</u> 21 20 €c) 21 *** 4** 23 310 u) 32 S) M 808 9 7 4 C CAN KA 42 42 3

TABLE 4. PROBABILITY OF NO-GO FOR ANY ONE OF CASE I ATMOSPHERIC CONSTRAINTS

FOR EOM LANDING AT KSC FOR ALL MONTHS

Constraints:

- . Thunderstorms
- Precipitation
- Ceiling < 20,000 feet or visibility < 8 nautical miles a major factor winter AM
- Peak head wind > 25 knots; peak tail wind no factor because both ends of runway are used.

,2,51

Peak crosswind > 10 knots - a major factor in PM

TABLE 5. PROBABILITY OF CASE II ATMOSPHERIC CONSTRAINTS FOR EOM LANDING AT KSC, JANUARY

		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	13 14 HP HP HP HP HR HR HP	•	45 48 50 49 54 52 45 45 41 38 34 37 36 34 35 35 33 34 35 37 36			0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		6 43 46 48 51 50 55 53 86 89 87 45 84 84 92 80 39 38 38 38 38 38 88	-1	20 30 30 30 30 30 30 30 30 30 30 30 30 30
RUNCATE 4-19-62 TIPE 19119156	PERIOD OF RECARD 1957 - 1970. DATA SOURCES : SEGMENT COMPLETE	FEAK MINES FULLAY AVOLE 155-0 AND 335-C DEGREES	FEUIPETENT 00 01	INUMDERSTOR 0 3	\$.	C 25 % 711E5 C 20	STEADY WINDS SERVOTS 0 0 0 TAIL WIND > 13 KNOTS 0 0	SURFACE CPCSSAIND 3 13 A'075- PEAK CROSSAIND 3 0	NY OF THE LADYE		- AT	

the second secon

ORIGINAL PAGE IS OF POOR QUALITY

大人 一次以外 日本日本日本

I

TABLE 6. PROBABILITY OF CASE II ATMOSPHERIC CONSTRAINTS FOR EOM LANDING AT KSC, JULY

POWALY AND IT 155.0 AND 195.0 DEGETES FORMALL THE LINE PRECENT FORMAL THE	SERIALLY COPPLETE THUNDERSTORM	PERIOD OF RECORD 1957 - 1970 DATA SUMPLE : SCRIALLY COMPLETE THUNDERS COM	, j
15 13 16 17 15 18 71 21 20 18 20 15 21 19 24 27 21 31 31 32 20 22 18 17 15 13 16 17 15 18 71 21 20 18 20 19 21 19 24 27 22 21 13 4 8 6 8 3 1 17 15 13 16 17 15 18 71 21 20 18 20 19 21 19 24 25 27 31 33 32 29 22 18 17 15 13 16 17 15 18 71 21 20 18 20 19 21 19 24 25 27 31 33 32 29 22 18 17 16 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	155.0		1
15 13 16 17 15 10 71 21 20 16 20 19 21 19 24 25 27 31 33 32 29 22 16 17 15 10 10 10 10 10 10 10 10 10 10 10 10 10		1 MR HR	
15 13 16 17 15 18 71 21 20 18 20 19 21 19 24 25 27 31 33 32 29 22 18 17 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	IMMO EL STOF	2 3 3 3 3 2 3 5 9 15 19 24 27 24 11	
15 13 16 17 15 18 71 21 20 13 20 19 21 19 24 25 27 31 33 32 29 22 18 17 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	PPECIPITATION CLOIC CEILING	1 1 1 1 2 2 2 1 1 2 3 6 6 6 11 12 14 10 6 6 3	
15 18 16 17 15 18 21 20 18 20 19 21 19 28 25 27 31 33 32 29 22 18 17 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	= 200ce FT		,
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	41165	18 16 17 15 18 21 20 18 20 19 21 19 24 25 27 40 20 20 20 20 20 20 20 20 20 20 20 20 20	
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	VISIBILITY C C. R. MILLS	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	700
S C D D D D D D D D D D D D D D D D D D	CLOUR CONER		w (
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	NDS		PUAL
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	CRESSAIND		ITY
17 20 18 20 17 20 23 24 24 23 24 27 30 37 41 43 42 41 36 32 25 21 2 17 20 18 20 17 20 23 24 24 23 24 27 30 37 41 13 42 41 39 32 25 21 2 HR H		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
17 20 18 20 17 20 23 29 29 29 27 30 37 91 93 92 91 15 25 21 19 20 21 20 21 20 21 20 21 20 20 21 20 20 20 20 20 20 20 20 20 20 20 20 20	ANY OF THE ABOVE		
17 20 18 20 17 20 23 29 29 29 29 29 27 30 37 91 93 92 91 39 22 25 21 20 20 20 20 20 20 20 20 20 20 20 20 20	ANY OF THE ABOVE FOR	24 24 24 24 24 24 24 24 27 30 37 41 43 42 41 34 32 25 21 00000000000000000000000000000000	1
- HR	F 11.5	18 20 17 20 23 29 29 29 27 30 37 91 93 92 91 30 32 25 21	, I
		HR H	

100

The second of th

第一生 一次 と 一 教がよくな

とうしょう からない とき 真定 していれいかかかい しょうしゅう

The second of th

TABLE 7. PROBABILITY OF CASE II, ANY ONE OF ATMOSPHERIC CONSTRAINTS FOR EOM LANDING AT KSC FOR ALL MONTHS

with the same of t

11	HOUT LST	17 18 17 50 51 52 53	39 36 35 38 36 39 36 62 61 39 39 39 41 36	2	ارة :	41 39 35 33 26 23	25 25	39 39 36 35 31 30 - 308 90 39 36 36 35 35	35 32 32 34 31 31 31 32 (30) 33 33 33	
RUNDATE 4-14-82 TIME 19:20: 7 MSC ANY OF THE AROUF EAR WOME	HR H	508	FEB 37 41 43 45 47 49 53 56 55 50 49 47 45 44 45 45	HAN 36 37 40 40 42 42 47 47 44 44 45 21 42 44 43 44 43 308 APR 28 28 29 31 31 32 37 37 34 35 35 35 35 15 16 16 18 18 29	22 23 20 23 26 32 30 39 30 31 32 32 35 35	JUN 22 23 26 26 25 28 30 31 33 31 34 36 37 43 46 (50) 48 44	16 19 24 20 21 23	CCT 34 36 36 39 38 40 42 41 42 34 44 45 47 45 43 41	DEC 36 37 39 39 38 39 44 47 45 41 (39 37 39 40 38 36 36	to the state of th

Constraints;

- 1. Thunderstorms
- . Pracipitation
- . Ceiling < 20,000 feet and/or visibility < 8 nautical miles
- Steady state head wind > 25 knots; both ends of runway used, no tail wind construint.

では、 ないのでは、 ない

さいていかい かいこうかん かいかいはない とうかい かまつ かいしつ しゅうしゅき しゅうしゅ

5. Steady state crosswind > 10 knots

TABLE 8. NO-GO AND GO FOR CASE I ATMOSPHERIC CONSTRAINTS FOR KSC EOM LANDING AT 0900 LST, JANUARY

+ = MISSING	3 % [•	; ,	HOMTH	1 1	•	1, MgU	11	•																					
46.45	70	C 2	01 C2 03 C4 05 C6 C7 2	C. 0.5	5	G6 C7	7.7	2	1	11 C	12	2	1	57	16		=	2	2	~	2	73		2	2	72	82	2	g	1 = 1
1:57		•		1 C r	j.	_		6		-	-	-				-	-			-	es i	-	0	0	6	0	.0	-	87	,0
1 959	c.	-	-		_	_			c	0	-	-	6	0	6	-	0	C	-	-	-	-	-	-	-	-	٢	-	-	-
1359	-		,	, =		1	-	-	-	0	9	; -	٦	-	.	0	C	6	0	-	-	-	-	-	0	0	-		p=4	0
1960	-	o		; ; c s	;	-	-		-	(0 - -	(0	! -	j 	-	0	0	-	C	6	0	0	Ü	6	0	-	0	6	0	~	~
1961	_	e,	0		6		_	_		-	-	-	-	-	-	-	n	-	c	-	0	0	-	0	0	-	-	-	-	-
1562	_	ę,	O	1	ا •	-		-		1	~	-	-	ID	-	٦	٦	-	0	-	6	-	0	-	0	. 	-	•	0	-
1 46 3	-	,	; 'e	e.	-	-	_		5	0	1	-	-	-	63	U	6	0	0	-	6	-	-	-	-	-	6	,-	-	,0
1564	-	,	0	0	6	0	_	_		1		-	-	0	-	-	-	0	-	-	0	-	-	0	0	-	-	-	-	
1565		•	-	_	, 							-	ie į	-	-	ļ -	ြင	်ဝ	0	6	်င	0	' ~	0	-	0	6	0	-	n
1365	r	t .	O	_		-	- E	-	-		;	-	1	~		6	D	-	-	-	` ~		~	-	-	,=	'n	_	-	0
1361	C	-		_	-	6			_		0	0	-	-	-	-	-	0	c	0	-	-	-	0	-	-	0	-	0	0
1768	_		, =		; Er	-6	•	-	_	1	-] 	-	-	C	-	-	-	0	C	0	-	-	-	0	_	-	•	-	_
1069	C	n	0	-		: ••		10	0		-	0	0	0	0	0	-	•	'- i	-	-	0	0	-	0	_	6	-	0	0
1 973	-	-		-		-	-		6	n n	-	-	-	-	-	0	-	-	-	-	[-	0	-	9	-	-	-	0	-	•
		•			i	1	!	!	i	i								į			1						; 	1	•	
															,				1		,									
									,			}	i	,	,	1	1		ł	,	•	;			!	1	;			
								•	;																					

TABLE 9. PROBABILITY OF NO-GO RUNS AND CONDITIONAL PROBABILITIES FOR ANY ONE OF CASE I ATMOSPHERIC CONSTRAINTS FOR KSC EOM LANDING AT 0900 LST, JANUARY

7 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5		714E 19:10:59		H0:17H	= 1 HOUP								
1 00 000		PRO16. 4		•	1			,		ı			
	SU# 2	DAYS	1-7	2-6	1-3	3-1-	2-r	9-0	-		6-7	J-13	
	253	. .	101	۲	· c	ŗ	0	0	0	¢,	٣	n	
	163	26	3 2	177	ເດີ	r t	0 n	0 E	n 6	~ •	ပပ	o e	
	16	1.9	30		9	100	6	، رع	c	(C) (e, e	0	
	9 6		27	e .	2	:		- 66	ה ^י כ	7 0) 	
	23		45		5 2	- E	25		190		0	· 63	
	6		• • •		11		# C	6 .	9 5	Ξ.	0 5	C) C	
	+	-	-	- 4	4	-	3		24	3.0	39	100	
			•			· v	•	0.7	=	717	36	5.1	
	era !	·				-		· •		- 11	1.5	53	i Į
	-	0	¢	- - :	;		~	•	m	•	•,	=	
,													ĺ
	•												
	•		1	-					: : :			,	

			KSC	KSC LST, PRELAUMCH, LAUMCH, AND RTLS	WCH, LA	MCH, AM	RTES						
WAR JG 31TO		4-15-92	65:31:61 3411	: 59	1101	**************************************		•	,				
LENGTH FREG.	1		PR38. T		!		-			-			
PUR LEACTHS SUP 1 SUM 2	Sur 1	SUR 2	DAVS	1-,	J-2	2-3	4-1	S-C	9-7	7-0	•	•••	21
\$5	6	191	*2	101	L:	£.	C	ę.	r	0	0	C	•
	\$	=	21	05	ĕ	01	C 1	r, c	C (0 (01	D	en (
	4:	2 2	-	25	1.	3	5.5	3		0	90	-	0
udo 		11		•		24	25	100	Ci	0	D	0	0
	~	•	-	•	►.	-	3	27	101 101	0	C (6 1	0

·

	,		1				
1				1			ı
				- 1			i
							i
				1			1
			,				1
							1
							1
							ı
		1	,				1
		!		iii	i	,	1
	,	;					1
	•		;				1
	i	:	,	1			
			i	į l			
	1				:	ŧ	
'	į	i	:				
٠ .			,			:	
			,	1	!	•	1
, 1	1	i	,		1		1
	į į	!			1	;	1
,						ì	1
,	ì	:			;	1	1
•	ì			1 1		1	1
				- { - }	and the second of the second o		1
:		1					1
,			1		:	;	ı
		1				ì	1
,	1		i			•	
	i,	1	1		l	!	1
						1	1
				į	. !		1
1						1	
:		1	ł j	ĺ		4	1
	;	1	li		!		
		!				1	
	i	1			1	j	1
		,			1	· ·	
	'	•			٠ ١	;	1
:		, ,	;			1	1
,	1						
	:	i l		1 1		-	
	i :		i	;	1		1
		1	,	i			1
	ì	ı				ì	1
:	! !	1	١,	,		;	
:					1		1
ļ	l :						ı
						;	-
:		!					1
i	'	i	}		1	•	1
	,		١,	,	ı		
	į.	*	!	i			
				:			
	 		1	•	ļ		1
		1	1				
			l				
			1		1		
			ļ				ı
	}	•			l		
					1		
	!						1
			Í		ì		1
							•
					!		1
	1		l				1
	4		i		ı		




Figure 1. Conditional No-Go probabilities for Case I atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January.




Figure 2. Conditional Go probabilities for Case I atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January.




Figure 3. Conditional No-Go probabilities for Case I atmospheric constraints for EOM at 0900 † ST, landing at KSC, Florida, July.






Figure 4. Conditional Go probabilities for Case I atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July.




Figure 5. Conditional No-Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January.




Figure 6. Conditional Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, January.






Figure 7. Conditional No-Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July.




Figure 8. Conditional Go probabilities for Case II atmospheric constraints for EOM at 0900 LST, landing at KSC, Florida, July.

REFERENCES

- 1. King, R. L.: Optimum Space Shuttle Launch Times Relative to Natural Environment. NASA CR-150374, Marshall Space Flight Center, Alabama, September 1977.
- Crutcher, H. L., Aimazan, J. A., and Quinlan, F. T.: Prediction of the Maximum Wind Speed in the 10-15 km Layer Above Cape Kennedy. NASA CR-61257, Marshall Space Flight Center, Alabama, January 1969.
- 3. Fall, L. W., Williford, W. O., and Carter, M. C.: Probability Distributions for Thunderstorm Activity at Cape Kennedy, Florida. NASA TM X-53867, May 1970.